

S

EXECUTION FOR SAFE AREA FOR GENERAL USE • INDOORS & OUTDOORS
SUITABLE FOR FLEXIBLE CONDUIT COUPLING



Kit version (code: KIT)
Includes cable glands and
the requested complete
series of the rubber seals
accompanying the size.



SALD¹
FOR LEAD SHEATED ARMoured CABLES
INNER AND OUTER SEALING



SN¹
FOR UNARMoured CABLES
OUTER SHEATH SEAL



SATD¹
FOR ARMoured CABLES
INNER AND OUTER SEALING



SNT¹
FOR UNARMoured CABLES
OUTER SHEATH SEAL



SAS¹
FOR ARMoured CABLES
INNER SEALING UNDER ARMOUR



SNM¹
FOR UNARMoured CABLES
OUTER SHEATH SEAL



SAC¹
FOR ARMoured CABLES
INNER SEALING UNDER ARMOUR



SNC¹
FOR UNARMoured CABLES
OUTER SHEATH SEAL



SAM¹
FOR ARMoured CABLES
INNER SEALING UNDER ARMOUR



SAD¹
FOR ARMoured CABLES
INNER AND OUTER SEALING



SAT¹
FOR ARMoured CABLES
INNER SEALING UNDER ARMOUR

EXAMPLE CODE

See page 56

0	1	2	3	3E	4	5	6	7	8
KIT	SATD.	25.	13.	24.	N25.	EP.	ON.	OR.	BS
Optional code	Type	Size	Ø C Max	Ø C Max	Thread code	Seals material code	Material code	Optional code	Optional code
Kit series			Inner seal (10,5 ÷ 13)	Outer seal (19 ÷ 24)	See tab. page 57	EP-SI	OT-ON-S6 AL-AVP	O-Ring	Reduced cone

SIZE	Ø C		Ø Ce		ARMOUR RANGE		Ø D - THREADS					WEIGHT										
	Min - Max Inner seal		Min - Max Outer seal		Standard cone X*	Reduced cone Y**	Cylindrical			Tapered		SN	SNT	SAT	SNC	SNM	SAC	SAM	SAS	SAD	SATD	SALD
	Min	Max	Min	Max			ISO 262	ISO 228	DIN 40430	NPT	EN 10226											
16 (EP)	4	7	5 ÷ 10 10 ÷ 15	0 ÷ 0,5	0,5 ÷ 0,75	M12x1,5	1 / 4"	Pg7	1 / 4"	1 / 4"	94				101			97	126	126		
16 (SI)	4	6				M16x1,5	3 / 8"	Pg9	3 / 8"	3 / 8"												
	6	8				M20x1,5	1 / 2"	Pg11	1 / 2"	1 / 2"												
	8	10				M25x1,5	3 / 4"	Pg13,5	3 / 4"	3 / 4"												
20	5,5	8	10 ÷ 15 14 ÷ 19	0 ÷ 0,5	0,5 ÷ 1,25	M16x1,5	1 / 2"	Pg11	1 / 2"	1 / 2"	156			174				160	228	232		
	8	10,5				M20x1,5	3 / 4"	Pg13,5	3 / 4"	3 / 4"												
	10,5	13				M25x1,5	1"	Pg16	1"	1"	185			206				191	264	270		
	13	15,5				M32x1,5	1"	Pg21	1"	1"	340			356				348	484	494		
	15,5	18				M40x1,5	1" 1/4	Pg29	1" 1/4	1" 1/4	421			431				429	576	591		
	21	24				M50x1,5	1" 1/2	Pg36	1" 1/2	1" 1/2	537			568				538	730	750		
	24	27				M63 x 1,5	2"	Pg42	2"	2"	749			784				726	961	989		
	27	30				M75x1,5	2" 1/2	Pg48	2" 1/2	2" 1/2	1085			1124				1058	1392	1429		
	30	33				M90x2	3"	/	3"	3"	2125			2235				2128	3026	3077		
	33	36									1759			1852				1762	2432	2492		
63	36	39	42 ÷ 48 47 ÷ 53	0 ÷ 1	1 ÷ 2	M50x1,5	2"	Pg42	2"	2"												
	39	42				M63x1,5	2" 1/2	Pg48	2" 1/2	2" 1/2												
	42	45																				
	45	48																				
	48	51																				
	51	54																				
	54	58																				
	58	62																				
	60	64																				
	64	68																				

• Standard Threads in bold • Dimensions are in millimeters • Weight in grams (gr) of brass version

• Inside the size, the external rubber seals may be matched with any interior rubber seals, compatible with the cable size. (See on page 57)

* Standard cone X: Suitable for all approved armour cables except SWA cables ** 8 Reduced cone Y: Suitable for SWA cables (code: BS)