

SAFETY DATA SHEET

EPOXY PUTTY RESIN RCN EPR+EPH

Compilation date: 20/11/2019 - Revision No: 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: EPOXY PUTTY RESIN RCN EPR+EPH
 Product code: RCN EPR
 Synonyms: RCN EPR+EPH

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Part A (resin) of a two pack, epoxy repair paste; to be used only with the corresponding Part B (catalyst) component.

1.3. Details of the supplier of the safety data sheet

Company name: RCN srl
 Regione Torame Via Crevacuore
 13011 Borgosesia VC
 ITALY
 R.E.A. Vercelli n. 188464 Reg. Imp. Vercelli
 VAT: IT02384130023
 Tel: +39 (0) 163 458028
 email: rcn@rcn.it

1.4. Emergency telephone number

Emergency tel: +39 (0) 163 458028 (office hours only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 3: H412; Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; -: EUH205
 Most important adverse effects: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful to aquatic life with long lasting effects. Contains epoxy constituents. May produce an allergic reaction.

2.2. Label elements

Label elements:

UFI: 8KEF-UVAQ-R00S-13KE

Hazard statements: H315: Causes skin irritation.
 H317: May cause an allergic skin reaction.
 H319: Causes serious eye irritation.
 H412: Harmful to aquatic life with long lasting effects.
 EUH205: Contains epoxy constituents. May produce an allergic reaction.

Hazard pictograms: GHS07: Exclamation mark



Signal words: Warning

Precautionary statements: P264: Wash hands thoroughly after handling.
 P273: Avoid release to the environment.
 P280: Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321: Specific treatment (see information on this label)

P332+P313: If skin irritation occurs: Get medical advice/attention.

Haz. ingredients (label): BISPHENOL A-(EPICHLORHYDRIN) (REACTION PRODUCT)

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

TALC

EINECS	CAS	PBT / WEL	CLP Classification	Percent
238-877-9	14807-96-6	Substance with a Community workplace exposure limit.	-	10-30%

LIMESTONE

215-279-6	1317-65-3	Substance with a Community workplace exposure limit.	-	10-30%
-----------	-----------	--	---	--------

BISPHENOL A-(EPICHLORHYDRIN) (REACTION PRODUCT) - REACH registered number(s): 01-2119456619-26

500-033-5	25068-38-6	-	Eye Irrit. 2: H319; Skin Irrit. 2: H315; Skin Sens. 1: H317; Aquatic Chronic 2: H411	10-30%
-----------	------------	---	---	--------

SILICA QUARTZ

238-878-4	14808-60-7	Substance with a Community workplace exposure limit.	Acute Tox. 4: H332	10-30%
-----------	------------	--	--------------------	--------

MAGNESIUM CARBONATE

208-915-9	546-93-0	Substance with a Community workplace exposure limit.	-	2.9-10%
-----------	----------	--	---	---------

SECTION 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Do not attempt to take action without suitable protective clothing - see section 8 of SDS.
Do not create dust.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Avoid the formation or spread of dust in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

TALC

State	Workplace exposure limits:		Respirable dust:	
	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	1 mg/m ³	-

LIMESTONE

UK	-	-	4 mg/m ³	-
----	---	---	---------------------	---

SILICA QUARTZ

UK	-	-	0,1 mg/m ³	-
----	---	---	-----------------------	---

MAGNESIUM CARBONATE

UK	-	-	4 mg/m ³	-
----	---	---	---------------------	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves. PVC gloves. Neoprene gloves. Nitrile gloves. Butyl gloves.
Breakthrough time of the glove material > 1 hour.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Solid
Colour: Dark red
Odour: Barely perceptible odour
Solubility in water: Insoluble
Flash point°C: > 100
Relative density: 1.92 - 1.98

9.2. Other information

Other information: No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Acids. Bases. Amines.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	11400	mg/kg

Hazardous ingredients:

BISPHENOL A-(EPICHLORHYDRIN) {REACTION PRODUCT}

ORL	MUS	LD50	15600	mg/kg
ORL	RAT	LD50	11400	mg/kg
SKN	RBT	LD50	>20	ml/kg

Relevant hazards for product:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Hazardous: calculated
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	The eyes may water profusely.
Ingestion:	There may be soreness and redness of the mouth and throat.
Inhalation:	Exposure may cause coughing or wheezing.
Delayed / immediate effects:	Immediate effects can be expected after short-term exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Heavier than water. Insoluble in water.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 13

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.
Waste disposal No. 15 01 08.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information

Transport class: This product does not require a classification for transport.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

SECTION 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH205: Contains epoxy constituents. May produce an allergic reaction.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H411: Toxic to aquatic life with long lasting effects.
H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.